

EXHIBIT "A"

BEING A TRACT OF LAND, SITUATED IN THE CITY OF WYLIE, COLLIN COUNTY, TEXAS, AND BEING PART OF TRACT 12 (43.1 ACRES) AND ALL OF TRACT 13 (5.4 ACRES), TRACT 16 (18.53 ACRES), TRACT 40 (11.9 ACRES), TRACT 53 (1.12 ACRES), TRACT 42 (1.0 ACRES), TRACT 33 (1.5 ACRES), TRACT 41 (39.1 ACRES), TRACT 39 (50.0 ACRES), TRACT 34 (7.87 ACRES) IN THE WILLIAM JOHNSON SURVEY, ABSTRACT NO. 476,

AND ALL OF TRACT 36 (0.86 ACRES), TRACT 35 (95.32 ACRES), TRACT 37 (9.87 ACRES), TRACT 38 (8.75 ACRES), TRACT 51 (3.67 ACRES), TRACT 39 (7.36 ACRES), TRACT 72 (59.52 ACRES), TRACT 40 (4.53 ACRES), TRACT 41 (1.52 ACRES), TRACT 42 (0.76 ACRES), TRACT 43 (0.76 ACRES), TRACT 44 (0.76 ACRES), TRACT 45 (59.0 ACRES), TRACT 46 (11.93 ACRES), TRACT 47 (6.14 ACRES), TRACT 48 (3.27 ACRES), TRACT 49 (14.97 ACRES), TRACT 50 (15.86 ACRES) IN THE W. W. BELL SURVEY, ABSTRACT NO. 37,

AND ALL OF TRACT 45 (0.1 ACRES), TRACT 69 (752.6701 ACRES) IN THE THOMAS CHAMBERS SURVEY, ABSTRACT NO. 1049,

AND ALL OF TRACT 6 (90.0 ACRES) IN THE MADISON WALKER SURVEY, ABSTRACT NO. 1022,

AND ALL OF TRACT 54 (39.56 ACRES), PART OF TRACT 22 (123.99 ACRES), PART OF TRACT 25 (510.0 ACRES), PART OF TRACT 18 (429.05 ACRES), PART OF TRACT 13 (88.0 ACRES), AND PART OF TRACT 17 (21.57 ACRES) IN THE M. I. GEMINEZ SURVEY, ABSTRACT NO. 338,

AND ALL OF TRACT 1 (458.0 ACRES) IN THE B. M. CARR SURVEY, ABSTRACT NO. 175,

AND ALL OF TRACT 1 (14.78 ACRES) AND TRACT 2 (159.66 ACRES) IN THE JAMES KING SURVEY, ABSTRACT NO. 508,

AND ALL OF TRACT 7 (2.0 ACRES), TRACT 11 (1.0 ACRES), TRACT 14 (1.06 ACRES), TRACT 15 (6.9 ACRES), TRACT 17 (9.16 ACRES), TRACT 19 (8.0 ACRES), TRACT 20 (12.35 ACRES), TRACT 21 (8.08 ACRES), TRACT 22 (28.3 ACRES), TRACT 24 (14.52 ACRES), TRACT NO. 40 (15.2 ACRES), TRACT 41 (21.66 ACRES), TRACT 44 (10.72 ACRES), TRACT NO. 47 (0.5 ACRES), TRACT 48 (0.6 ACRES), TRACT 49 (1.0 ACRES), TRACT 50 (31.3 ACRES) AND TRACT 60 (12.5 ACRES) IN THE JOHN D. KIRBY SURVEY, ABSTRACT NO. 515,

AND ALL OF TRACT 11 (36.19 ACRES), TRACT 12 (226.7 ACRES), TRACT 13 (0.5893 ACRES), TRACT 14 (1.0 ACRES), TRACT 15 (0.5893 ACRES), TRACT 16 (0.5893 ACRES), TRACT 17 (0.5893 ACRES), TRACT 18 (1.2339 ACRES) IN THE ALEX RUSSELL SURVEY, ABSTRACT NO. 736, SAID TRACT BEING MORE PARTICULARLY DESCRIBED, AS FOLLOWS:

BEGINNING AT A POINT FOR CORNER, BEING THE NORTHWESTERLY CORNER OF TRACT 18 (ALEX RUSSELL SURVEY, ABSTRACT NO. 736,

THENCE S 89° 36' 47" E, A DISTANCE OF 2127.00' TO A POINT FOR CORNER;

THENCE S 89° 15' 16" E, A DISTANCE OF 1207.25' TO A POINT FOR CORNER, BEING THE NORTHEASTERLY CORNER OF TRACT 2 (JAMES KING SURVEY, ABSTRACT NO. 508);

THENCE S 00° 02' 37" W, A DISTANCE OF 719.59' TO A POINT FOR CORNER;

THENCE N 90° 00' 00" E, A DISTANCE OF 2285.77' TO A POINT FOR CORNER;

THENCE N 89° 44' 38" E, A DISTANCE OF 654.68' TO A POINT FOR CORNER;

THENCE N 89° 44' 38" E, A DISTANCE OF 612.09' TO A POINT FOR CORNER TO THE NORTHEASTERLY CORNER OF TRACT 12 (ALEX RUSSELL SURVEY, ABSTRACT NO. 736), SAME BEING IN AN OLD CREEK BED;

THENCE ALONG SAID OLD CREEK BED, THE FOLLOWING COURSES AND DISTANCES:

S 30° 18' 45" E, A DISTANCE OF 212.86' TO A POINT FOR CORNER;

S 08° 08' 52" E, A DISTANCE OF 278.98' TO A POINT FOR CORNER;

S 09° 38' 53" E, A DISTANCE OF 139.49' TO A POINT FOR CORNER;

S 11° 08' 15" E, A DISTANCE OF 276.09' TO A POINT FOR CORNER;

S 28° 30' 01" E, A DISTANCE OF 100.17' TO A POINT FOR CORNER;

S 15° 30' 01" E, A DISTANCE OF 100.17' TO A POINT FOR CORNER;

S 02° 30' 01" E, A DISTANCE OF 100.17' TO A POINT FOR CORNER;

S 10° 29' 59" W, A DISTANCE OF 100.17' TO A POINT FOR CORNER;

S 23° 29' 59" W, A DISTANCE OF 100.17' TO A POINT FOR CORNER;

S 36° 29' 27" W, A DISTANCE OF 100.03' TO A POINT FOR CORNER;

S 24° 24' 24" W, A DISTANCE OF 381.52' TO A POINT FOR CORNER;

S 21° 24' 24" W, A DISTANCE OF 381.52' TO A POINT FOR CORNER;

S 18° 48' 05" W, A DISTANCE OF 281.10' TO A POINT FOR CORNER;

S 02° 12' 10" W, A DISTANCE OF 114.13' TO A POINT FOR CORNER;

N 89° 55' 22" W, A DISTANCE OF 17.05' TO A POINT FOR CORNER;

S 23° 35' 11" W, A DISTANCE OF 234.23' TO A POINT FOR CORNER;

S 20° 05' 50" W, A DISTANCE OF 214.23' TO A POINT FOR CORNER;

S 15° 50' 59" W, A DISTANCE OF 312.82' TO A POINT FOR CORNER;

S 10° 20' 59" W, A DISTANCE OF 375.33' TO A POINT FOR CORNER;

S 04° 51' 00" W, A DISTANCE OF 312.82' TO A POINT FOR CORNER;

S 00° 09' 01" E, A DISTANCE OF 312.82' TO A POINT FOR CORNER;
S 03° 24' 19" E, A DISTANCE OF 94.51' TO A POINT FOR CORNER;
S 06° 22' 54" E, A DISTANCE OF 1975.53' TO A POINT FOR CORNER;
S 14° 37' 05" E, A DISTANCE OF 207.79' TO A POINT FOR CORNER;
S 06° 37' 05" E, A DISTANCE OF 207.79' TO A POINT FOR CORNER;
S 01° 22' 55" W, A DISTANCE OF 207.79' TO A POINT FOR CORNER;
S 09° 22' 55" W, A DISTANCE OF 207.79' TO A POINT FOR CORNER;
S 17° 22' 55" W, A DISTANCE OF 207.78' TO A POINT FOR CORNER;
S 25° 22' 55" W, A DISTANCE OF 207.79' TO A POINT FOR CORNER;
S 33° 22' 55" W, A DISTANCE OF 207.78' TO A POINT FOR CORNER;
S 39° 07' 56" W, A DISTANCE OF 248.74' TO A POINT FOR CORNER;
S 41° 01' 08" W, A DISTANCE OF 95.42' TO A POINT FOR CORNER;
S 24° 34' 43" W, A DISTANCE OF 296.62' TO A POINT FOR CORNER;
S 11° 04' 43" W, A DISTANCE OF 275.52' TO A POINT FOR CORNER;
S 03° 38' 29" E, A DISTANCE OF 348.30' TO A POINT FOR CORNER;
S 12° 49' 31" E, A DISTANCE OF 385.13' TO A POINT FOR CORNER;
S 09° 49' 31" E, A DISTANCE OF 385.13' TO A POINT FOR CORNER;
S 06° 19' 31" E, A DISTANCE OF 513.46' TO A POINT FOR CORNER;
S 02° 39' 04" E, A DISTANCE OF 429.76' TO A POINT FOR CORNER;
S 05° 58' 50" W, A DISTANCE OF 1335.25' TO A POINT FOR CORNER;
S 20° 37' 50" W, A DISTANCE OF 226.63' TO A POINT FOR CORNER;
S 16° 39' 41" W, A DISTANCE OF 351.36' TO A POINT FOR CORNER;
S 16° 06' 51" W, A DISTANCE OF 354.76' TO A POINT FOR CORNER;
S 07° 47' 02" W, A DISTANCE OF 212.93' TO A POINT FOR CORNER;
S 03° 12' 46" E, A DISTANCE OF 213.15' TO A POINT FOR CORNER;

S 13° 28' 42" E, A DISTANCE OF 184.45' TO A POINT FOR CORNER;

S 33° 21' 45" E, A DISTANCE OF 122.02' TO A POINT FOR CORNER;

S 31° 21' 45" E, A DISTANCE OF 366.02' TO A POINT FOR CORNER;

S 28° 20' 50" E, A DISTANCE OF 518.01' TO A POINT FOR CORNER;

S 25° 40' 15" E, A DISTANCE OF 128.43' TO A POINT FOR CORNER;

S 05° 10' 39" E, A DISTANCE OF 180.42' TO A POINT FOR CORNER;

S 16° 49' 43" W, A DISTANCE OF 150.88' TO A POINT FOR CORNER;

S 38° 12' 22" W, A DISTANCE OF 234.73' TO A POINT FOR CORNER;

S 44° 29' 36" W, A DISTANCE OF 244.85' TO A POINT FOR CORNER;

S 68° 29' 21" W, A DISTANCE OF 337.15' TO A POINT FOR CORNER;

S 60° 29' 21" W, A DISTANCE OF 337.15' TO A POINT FOR CORNER;

S 51° 59' 21" W, A DISTANCE OF 379.21' TO A POINT FOR CORNER;

S 42° 59' 21" W, A DISTANCE OF 379.21' TO A POINT FOR CORNER;

S 35° 11' 30" W, A DISTANCE OF 344.99' TO A POINT FOR CORNER, BEING THE SOUTHEASTERLY CORNER OF TRACT 25 (M. I. GEMINEZ SURVEY, ABSTRACT NO. 338);

THENCE DEPARTING SAID CREEK BED, N 89° 59' 03" W, ALONG THE SOUTHERLY LINE OF SAID TRACT 25, A DISTANCE OF 4293.72' TO A POINT FOR CORNER, BEING THE SOUTHWESTERLY CORNER OF SAID TRACT 25;

THENCE N 00° 03' 18" W, A DISTANCE OF 1378.65' TO A POINT FOR CORNER, BEING THE SOUTHEASTERLY CORNER OF TRACT 22 (M. I. GEMINEZ SURVEY, ABSTRACT NO. 338);

THENCE N 90° 00' 00" W, ALONG THE SOUTHERLY LINE OF SAID TRACT 22, A DISTANCE OF 1704.90' TO A POINT FOR CORNER, BEING THE SOUTHWESTERLY CORNER OF SAID TRACT 22;

THENCE N 00° 00' 00" W, ALONG THE WESTERLY LINE OF SAID TRACT 22, A DISTANCE OF 941.18' TO A POINT FOR CORNER, BEING THE SOUTHEASTERLY CORNER OF TRACT 54 (M. I. GEMINEZ SURVEY, ABSTRACT NO. 338);

THENCE N 90° 00' 00" W, ALONG THE SOUTHERLY LINE OF SAID TRACT 54, A DISTANCE OF 556.89' TO A POINT FOR CORNER, BEING THE SOUTHWESTERLY CORNER OF SAID TRACT 54;

THENCE N 00° 12' 58" W, ALONG THE WESTERLY LINE OF SAID TRACT 54, A DISTANCE OF 717.36' TO A POINT FOR CORNER, BEING THE MOST EASTERLY SOUTHEAST CORNER OF TRACT 6 (MADISON WALKER SURVEY, ABSTRACT NO. 1022);

THENCE S 89° 48' 06" W, ALONG THE SOUTHERLY LINE OF SAID TRACT 6, A DISTANCE OF 1778.31' TO A POINT FOR CORNER;

THENCE S 00° 00' 00" E, ALONG THE MOST SOUTHERLY EAST LINE OF SAID TRACT 6, A DISTANCE OF 933.97' TO A POINT FOR CORNER;

THENCE N 90° 00' 00" W, ALONG THE MOST WESTERLY SOUTH LINE OF SAID TRACT 6, A DISTANCE OF 318.35' TO A POINT FOR CORNER, BEING IN THE EASTERLY LINE OF TRACT 69 (THOMAS CHAMBERS SURVEY, ABSTRACT NO. 1049);

THENCE S 00° 08' 38" W, ALONG THE EASTERLY LINE OF SAID TRACT 69, A DISTANCE OF 1288.91' TO A POINT FOR CORNER, BEING THE SOUTHEASTERLY CORNER OF TRACT 69;

THENCE S 89° 56' 37" W, A DISTANCE OF 5241.62' TO A POINT FOR CORNER, BEING IN THE EAST FORK OF THE TRINITY RIVER;

THENCE ALONG SAID EAST FORK OF THE TRINITY RIVER, THE FOLLOWING COURSES AND DISTANCES:

N 05° 14' 22" E, A DISTANCE OF 314.37' TO A POINT FOR CORNER;

N 12° 45' 24" E, A DISTANCE OF 367.99' TO A POINT FOR CORNER;

N 00° 41' 37" W, A DISTANCE OF 413.65' TO A POINT FOR CORNER;

N 15° 41' 37" W, A DISTANCE OF 362.22' TO A POINT FOR CORNER;

N 29° 11' 37" W, A DISTANCE OF 336.47' TO A POINT FOR CORNER;

N 11° 49' 56" W, A DISTANCE OF 423.22' TO A POINT FOR CORNER;

N 04° 55' 47" W, A DISTANCE OF 583.05' TO A POINT FOR CORNER;

N 02° 34' 13" E, A DISTANCE OF 510.26' TO A POINT FOR CORNER;

N 08° 34' 13" E, A DISTANCE OF 364.58' TO A POINT FOR CORNER;

N 01° 55' 21" E, A DISTANCE OF 280.25' TO A POINT FOR CORNER;

N 14° 48' 38" W, A DISTANCE OF 427.94' TO A POINT FOR CORNER;

N 32° 51' 29" W, A DISTANCE OF 422.51' TO A POINT FOR CORNER;

N 29° 53' 48" W, A DISTANCE OF 536.79' TO A POINT FOR CORNER;

N 11° 23' 48" W, A DISTANCE OF 328.13' TO A POINT FOR CORNER;

N 05° 36' 13" E, A DISTANCE OF 467.55' TO A POINT FOR CORNER;
N 00° 27' 13" E, A DISTANCE OF 433.60' TO A POINT FOR CORNER;
N 07° 43' 19" W, A DISTANCE OF 682.20' TO A POINT FOR CORNER;
N 14° 43' 18" W, A DISTANCE OF 273.17' TO A POINT FOR CORNER;
N 02° 56' 53" E, A DISTANCE OF 101.10' TO A POINT FOR CORNER;
N 11° 48' 22" W, A DISTANCE OF 101.10' TO A POINT FOR CORNER;
N 26° 33' 36" W, A DISTANCE OF 101.10' TO A POINT FOR CORNER;
N 41° 18' 50" W, A DISTANCE OF 101.10' TO A POINT FOR CORNER;
N 56° 04' 05" W, A DISTANCE OF 101.10' TO A POINT FOR CORNER;
N 70° 49' 19" W, A DISTANCE OF 101.10' TO A POINT FOR CORNER;
N 85° 34' 33" W, A DISTANCE OF 101.10' TO A POINT FOR CORNER;
S 79° 40' 12" W, A DISTANCE OF 101.10' TO A POINT FOR CORNER;
S 64° 54' 58" W, A DISTANCE OF 101.10' TO A POINT FOR CORNER;
S 50° 09' 43" W, A DISTANCE OF 101.10' TO A POINT FOR CORNER;
S 89° 38' 25" W, A DISTANCE OF 96.91' TO A POINT FOR CORNER;
N 80° 22' 34" W, A DISTANCE OF 96.91' TO A POINT FOR CORNER;
N 70° 23' 33" W, A DISTANCE OF 96.91' TO A POINT FOR CORNER;
N 60° 24' 31" W, A DISTANCE OF 96.91' TO A POINT FOR CORNER;
N 50° 25' 30" W, A DISTANCE OF 96.91' TO A POINT FOR CORNER;
N 40° 26' 28" W, A DISTANCE OF 96.91' TO A POINT FOR CORNER;
N 30° 27' 27" W, A DISTANCE OF 96.91' TO A POINT FOR CORNER;
N 20° 28' 25" W, A DISTANCE OF 96.91' TO A POINT FOR CORNER;
N 10° 29' 24" W, A DISTANCE OF 96.91' TO A POINT FOR CORNER;
N 00° 30' 22" W, A DISTANCE OF 96.91' TO A POINT FOR CORNER;
N 90° 00' 00" W, A DISTANCE OF 80.23' TO A POINT FOR CORNER;

N 32° 45' 05" W, A DISTANCE OF 69.38' TO A POINT FOR CORNER;
N 54° 24' 51" W, A DISTANCE OF 53.46' TO A POINT FOR CORNER;
N 67° 03' 59" W, A DISTANCE OF 71.62' TO A POINT FOR CORNER;
N 40° 43' 52" W, A DISTANCE OF 69.27' TO A POINT FOR CORNER;
N 14° 07' 20" W, A DISTANCE OF 71.55' TO A POINT FOR CORNER;
N 00° 27' 25" W, A DISTANCE OF 71.25' TO A POINT FOR CORNER;
N 13° 32' 32" E, A DISTANCE OF 94.87' TO A POINT FOR CORNER;
N 27° 32' 35" E, A DISTANCE OF 71.25' TO A POINT FOR CORNER;
N 40° 02' 34" E, A DISTANCE OF 77.17' TO A POINT FOR CORNER;
N 42° 25' 08" E, A DISTANCE OF 46.51' TO A POINT FOR CORNER;
N 21° 19' 59" E, A DISTANCE OF 59.83' TO A POINT FOR CORNER;
N 05° 49' 58" E, A DISTANCE OF 63.80' TO A POINT FOR CORNER;
N 13° 10' 03" W, A DISTANCE OF 87.47' TO A POINT FOR CORNER;
N 23° 44' 01" W, A DISTANCE OF 78.51' TO A POINT FOR CORNER;
N 33° 50' 45" W, A DISTANCE OF 121.24' TO A POINT FOR CORNER;
N 46° 20' 44" W, A DISTANCE OF 80.95' TO A POINT FOR CORNER;
N 56° 20' 46" W, A DISTANCE OF 80.95' TO A POINT FOR CORNER;
N 66° 20' 44" W, A DISTANCE OF 80.95' TO A POINT FOR CORNER;
N 75° 50' 45" W, A DISTANCE OF 72.87' TO A POINT FOR CORNER;
N 85° 20' 45" W, A DISTANCE OF 80.95' TO A POINT FOR CORNER;
S 87° 39' 39" W, A DISTANCE OF 47.94' TO A POINT FOR CORNER;

THENCE DEPARTING SAID EAST FORK OF THE TRINITY RIVER, N 00° 08' 16" E, A DISTANCE OF 2811.06'
TO A POINT FOR CORNER;

THENCE N 00° 08' 16" E, A DISTANCE OF 1265.25' TO A POINT FOR CORNER;

THENCE N 00° 08' 16" E, A DISTANCE OF 447.96' TO A POINT FOR CORNER;

THENCE N 00° 04' 58" E, A DISTANCE OF 1960.18' TO A POINT FOR CORNER;

THENCE N 00° 08' 09" W, A DISTANCE OF 862.58' TO A POINT FOR CORNER;
THENCE N 00° 08' 09" W, A DISTANCE OF 850.72' TO A POINT FOR CORNER;
THENCE N 00° 08' 09" W, A DISTANCE OF 1035.37' TO A POINT FOR CORNER;
THENCE N 69° 48' 14" E, A DISTANCE OF 1567.53' TO A POINT FOR CORNER;
THENCE S 66° 19' 53" E, A DISTANCE OF 48.64' TO A POINT FOR CORNER;
THENCE N 67° 51' 17" E, A DISTANCE OF 116.00' TO A POINT FOR CORNER;
THENCE N 68° 18' 36" E, A DISTANCE OF 242.10' TO A POINT FOR CORNER;
THENCE N 68° 31' 50" E, A DISTANCE OF 652.30' TO A POINT FOR CORNER;
THENCE S 46° 56' 37" W, A DISTANCE OF 682.35' TO A POINT FOR CORNER;
THENCE S 02° 28' 15" E, A DISTANCE OF 417.44' TO A POINT FOR CORNER;
THENCE S 64° 14' 28" E, A DISTANCE OF 399.56' TO A POINT FOR CORNER;
THENCE S 35° 55' 39" E, A DISTANCE OF 946.48' TO A POINT FOR CORNER;
THENCE S 13° 01' 25" W, A DISTANCE OF 712.95' TO A POINT FOR CORNER;
THENCE N 62° 59' 29" W, A DISTANCE OF 11.26' TO A POINT FOR CORNER;
THENCE S 03° 55' 43" W, A DISTANCE OF 32.98' TO A POINT FOR CORNER;
THENCE S 21° 27' 36" E, A DISTANCE OF 404.80' TO A POINT FOR CORNER;
THENCE S 25° 08' 14" E, A DISTANCE OF 174.58' TO A POINT FOR CORNER;
THENCE S 37° 54' 24" E, A DISTANCE OF 303.15' TO A POINT FOR CORNER;
THENCE S 40° 25' 50" E, A DISTANCE OF 160.96' TO A POINT FOR CORNER;
THENCE S 42° 08' 44" E, A DISTANCE OF 165.20' TO A POINT FOR CORNER;
THENCE S 03° 54' 41" E, A DISTANCE OF 122.50' TO A POINT FOR CORNER;
THENCE S 20° 58' 50" W, A DISTANCE OF 67.01' TO A POINT FOR CORNER;
THENCE S 06° 19' 03" W, A DISTANCE OF 158.38' TO A POINT FOR CORNER;
THENCE S 02° 21' 30" W, A DISTANCE OF 311.99' TO A POINT FOR CORNER;
THENCE N 84° 27' 38" W, A DISTANCE OF 80.32' TO A POINT FOR CORNER;

THENCE N 01° 37' 09" W, A DISTANCE OF 461.53' TO A POINT FOR CORNER;
THENCE N 86° 02' 08" W, A DISTANCE OF 541.36' TO A POINT FOR CORNER;
THENCE S 00° 47' 10" W, A DISTANCE OF 972.13' TO A POINT FOR CORNER;
THENCE S 23 27' 52" W, A DISTANCE OF 398.08' TO A POINT FOR CORNER;
THENCE N 88° 56' 37" E, A DISTANCE OF 294.16' TO A POINT FOR CORNER;
THENCE S 01° 26' 14" W, A DISTANCE OF 363.61' TO A POINT FOR CORNER;
THENCE S 37° 03' 02" W, A DISTANCE OF 540.41' TO A POINT FOR CORNER;
THENCE S 12° 33' 05" E, A DISTANCE OF 149.09' TO A POINT FOR CORNER;
THENCE S 11° 18' 04" E, A DISTANCE OF 124.52' TO A POINT FOR CORNER;
THENCE S 10° 04' 01" E, A DISTANCE OF 613.43' TO A POINT FOR CORNER;
THENCE S 08° 48' 34" E, A DISTANCE OF 390.49' TO A POINT FOR CORNER;
THENCE S 71° 56' 18" W, A DISTANCE OF 319.33' TO A POINT FOR CORNER;
THENCE S 00° 08' 09" E, A DISTANCE OF 143.22' TO A POINT FOR CORNER;
THENCE N 89° 07' 28" W, A DISTANCE OF 85.12' TO A POINT FOR CORNER;
THENCE S 27° 47' 39" W, A DISTANCE OF 724.46' TO A POINT FOR CORNER;
THENCE S 64° 28' 23" W, A DISTANCE OF 900.02' TO A POINT FOR CORNER;
THENCE S 64° 28' 24" W, A DISTANCE OF 44.55' TO A POINT FOR CORNER;
THENCE S 25° 01' 24" W, A DISTANCE OF 701.17' TO A POINT FOR CORNER;
THENCE S 20° 59' 01" E, A DISTANCE OF 527.10' TO A POINT FOR CORNER;
THENCE S 89° 27' 00" E, A DISTANCE OF 215.31' TO A POINT FOR CORNER;
THENCE S 32° 48' 17" E, A DISTANCE OF 874.30' TO A POINT FOR CORNER;
THENCE S 89° 12' 48" E, A DISTANCE OF 441.37' TO A POINT FOR CORNER;
THENCE N 22° 39' 10" E, A DISTANCE OF 616.23' TO A POINT FOR CORNER;
THENCE S 87° 47' 18" E, A DISTANCE OF 605.26' TO A POINT FOR CORNER;
THENCE S 34° 50' 01" W, A DISTANCE OF 422.62' TO A POINT FOR CORNER;

THENCE S 43° 53' 27" E, A DISTANCE OF 295.55' TO A POINT FOR CORNER;
THENCE S 08° 36' 15" W, A DISTANCE OF 88.53' TO A POINT FOR CORNER;
THENCE S 32° 44' 21" W, A DISTANCE OF 343.60' TO A POINT FOR CORNER;
THENCE S 32° 38' 42" W, A DISTANCE OF 675.28' TO A POINT FOR CORNER;
THENCE N 89° 07' 12" W, A DISTANCE OF 123.20' TO A POINT FOR CORNER;
THENCE S 43° 37' 12" W, A DISTANCE OF 95.70' TO A POINT FOR CORNER;
THENCE S 02° 09' 10" W, A DISTANCE OF 200.74' TO A POINT FOR CORNER;
THENCE S 86° 47' 55" E, A DISTANCE OF 311.76' TO A POINT FOR CORNER;
THENCE N 74° 59' 47" E, A DISTANCE OF 258.59' TO A POINT FOR CORNER;
THENCE N 89° 34' 01" E, A DISTANCE OF 290.00' TO A POINT FOR CORNER;
THENCE N 19° 49' 48" E, A DISTANCE OF 29.85' TO A POINT FOR CORNER;
THENCE N 89° 53' 46" E, A DISTANCE OF 140.78' TO A POINT FOR CORNER;
THENCE N 00° 31' 12" W, A DISTANCE OF 59.86' TO A POINT FOR CORNER;
THENCE N 89° 26' 46" E, A DISTANCE OF 72.27' TO A POINT FOR CORNER;
THENCE N 00° 31' 12" W, A DISTANCE OF 60.00' TO A POINT FOR CORNER;
THENCE S 89° 26' 33" W, A DISTANCE OF 71.39' TO A POINT FOR CORNER;
THENCE N 00° 31' 12" W, A DISTANCE OF 35.25' TO A POINT FOR CORNER;
THENCE S 87° 56' 33" E, A DISTANCE OF 651.08' TO A POINT FOR CORNER;
THENCE S 00° 09' 54" W, A DISTANCE OF 153.57' TO A POINT FOR CORNER;
THENCE N 89° 16' 12" E, A DISTANCE OF 184.75' TO A POINT FOR CORNER;
THENCE S 01° 36' 20" E, A DISTANCE OF 349.09' TO A POINT FOR CORNER;
THENCE S 05° 14' 06" E, A DISTANCE OF 181.54' TO A POINT FOR CORNER;
THENCE S 10° 44' 07" E, A DISTANCE OF 217.82' TO A POINT FOR CORNER;
THENCE S 12° 18' 07" E, A DISTANCE OF 584.83' TO A POINT FOR CORNER;
THENCE N 76° 40' 45" E, A DISTANCE OF 200.93' TO A POINT FOR CORNER;

THENCE S 11° 31' 55" E, A DISTANCE OF 199.07' TO A POINT FOR CORNER;
THENCE S 77° 48' 23" W, A DISTANCE OF 203.54' TO A POINT FOR CORNER;
THENCE S 10° 59' 16" E, A DISTANCE OF 282.02' TO A POINT FOR CORNER;
THENCE S 36° 04' 44" E, A DISTANCE OF 372.38' TO A POINT FOR CORNER;
THENCE S 18° 39' 22" W, A DISTANCE OF 142.94' TO A POINT FOR CORNER;
THENCE S 22° 26' 38" W, A DISTANCE OF 318.79' TO A POINT FOR CORNER;
THENCE N 87° 56' 54" W, A DISTANCE OF 172.23' TO A POINT FOR CORNER;
THENCE S 14° 43' 10" W, A DISTANCE OF 467.23' TO A POINT FOR CORNER;
THENCE S 22° 31' 25" W, A DISTANCE OF 79.72' TO A POINT FOR CORNER;
THENCE S 43° 13' 35" E, A DISTANCE OF 192.14' TO A POINT FOR CORNER;
THENCE S 10° 39' 13" W, A DISTANCE OF 13.89' TO A POINT FOR CORNER;
THENCE S 45° 28' 22" E, A DISTANCE OF 272.09' TO A POINT FOR CORNER;
THENCE N 00° 22' 01" W, A DISTANCE OF 140.59' TO A POINT FOR CORNER;
THENCE S 86° 12' 46" E, A DISTANCE OF 29.70' TO A POINT FOR CORNER;
THENCE S 24° 18' 37" E, A DISTANCE OF 656.43' TO A POINT FOR CORNER;
THENCE S 45° 56' 18" E, A DISTANCE OF 41.41' TO A POINT FOR CORNER;
THENCE S 70° 12' 58" E, A DISTANCE OF 41.41' TO A POINT FOR CORNER;
THENCE S 00° 33' 21" W, A DISTANCE OF 30.20' TO A POINT FOR CORNER;
THENCE S 76° 59' 10" E, A DISTANCE OF 34.17' TO A POINT FOR CORNER;
THENCE S 00° 22' 18" W, A DISTANCE OF 511.22' TO A POINT FOR CORNER;
THENCE N 89° 15' 36" E, A DISTANCE OF 255.67' TO A POINT FOR CORNER;
THENCE S 00° 49' 09" W, A DISTANCE OF 526.63' TO A POINT FOR CORNER;
THENCE S 11° 30' 10" W, A DISTANCE OF 329.72' TO A POINT FOR CORNER;
THENCE N 90° 00' 00" E, A DISTANCE OF 350.00' TO A POINT FOR CORNER;
THENCE N 00° 00' 00" W, A DISTANCE OF 1345.01' TO A POINT FOR CORNER;

THENCE S 87° 47' 01" E, A DISTANCE OF 25.21' TO A POINT FOR CORNER;
THENCE S 00° 48' 24" E, A DISTANCE OF 1099.67' TO A POINT FOR CORNER;
THENCE S 86° 26' 09" E, A DISTANCE OF 817.14' TO A POINT FOR CORNER;
THENCE N 00° 12' 43" E, A DISTANCE OF 375.70' TO A POINT FOR CORNER;
THENCE N 26° 45' 55" W, A DISTANCE OF 846.96' TO A POINT FOR CORNER;
THENCE N 87° 15' 33" W, A DISTANCE OF 358.34' TO A POINT FOR CORNER;
THENCE N 07° 35' 36" E, A DISTANCE OF 570.38' TO A POINT FOR CORNER;
THENCE N 20° 22' 12" W, A DISTANCE OF 717.05' TO A POINT FOR CORNER;
THENCE N 86° 27' 28" W, A DISTANCE OF 260.27' TO A POINT FOR CORNER;
THENCE N 01° 17' 39" E, A DISTANCE OF 448.25' TO A POINT FOR CORNER;
THENCE N 00° 33' 16" W, A DISTANCE OF 692.00' TO A POINT FOR CORNER;
THENCE N 89° 15' 37" W, A DISTANCE OF 49.05' TO A POINT FOR CORNER;
THENCE N 00° 22' 29" E, A DISTANCE OF 139.81' TO A POINT FOR CORNER;
THENCE S 89° 54' 19" E, A DISTANCE OF 53.74' TO A POINT FOR CORNER;
THENCE N 00° 15' 01" E, A DISTANCE OF 141.61' TO A POINT FOR CORNER;
THENCE N 89° 31' 58" E, A DISTANCE OF 50.08' TO A POINT FOR CORNER;
THENCE N 00° 22' 36" E, A DISTANCE OF 310.00' TO A POINT FOR CORNER;
THENCE S 84° 43' 00" E, A DISTANCE OF 114.79' TO A POINT FOR CORNER;
THENCE N 09° 54' 47" E, A DISTANCE OF 172.74' TO A POINT FOR CORNER;
THENCE N 84° 56' 09" W, A DISTANCE OF 34.31' TO A POINT FOR CORNER;
THENCE N 05° 00' 00" W, A DISTANCE OF 370.00' TO A POINT FOR CORNER;
THENCE N 29° 00' 32" W, A DISTANCE OF 636.47' TO A POINT FOR CORNER;
THENCE N 87° 15' 06" E, A DISTANCE OF 178.70' TO A POINT FOR CORNER;
THENCE S 75° 17' 45" E, A DISTANCE OF 277.60' TO A POINT FOR CORNER;
THENCE S 80° 14' 51" E, A DISTANCE OF 107.07' TO A POINT FOR CORNER;

THENCE S 89° 30' 52" E, A DISTANCE OF 97.28' TO A POINT FOR CORNER;
THENCE N 76° 28' 10" E, A DISTANCE OF 271.22' TO A POINT FOR CORNER;
THENCE S 86° 51' 44" E, A DISTANCE OF 219.72' TO A POINT FOR CORNER;
THENCE S 41° 18' 00" W, A DISTANCE OF 314.00' TO A POINT FOR CORNER;
THENCE S 55° 02' 00" E, A DISTANCE OF 336.40' TO A POINT FOR CORNER;
THENCE S 04° 06' 50" W, A DISTANCE OF 450.54' TO A POINT FOR CORNER;
THENCE S 00° 04' 57" E, A DISTANCE OF 230.89' TO A POINT FOR CORNER;
THENCE S 87° 27' 19" E, A DISTANCE OF 533.25' TO A POINT FOR CORNER;
THENCE S 09° 08' 02" E, A DISTANCE OF 218.81' TO A POINT FOR CORNER;
THENCE S 04° 35' 13" E, A DISTANCE OF 108.78' TO A POINT FOR CORNER;
THENCE S 50° 43' 31" W, A DISTANCE OF 630.72' TO A POINT FOR CORNER;
THENCE S 08° 27' 05" E, A DISTANCE OF 164.79' TO A POINT FOR CORNER;
THENCE S 87° 22' 41" E, A DISTANCE OF 1110.90' TO A POINT FOR CORNER;
THENCE S 15° 41' 48" W, A DISTANCE OF 354.04' TO A POINT FOR CORNER;
THENCE S 02° 08' 56" W, A DISTANCE OF 467.16' TO A POINT FOR CORNER;
THENCE N 89° 28' 20" E, A DISTANCE OF 541.08' TO A POINT FOR CORNER;
THENCE N 00° 03' 14" W, A DISTANCE OF 50.00' TO A POINT FOR CORNER;
THENCE N 44° 33' 48" E, A DISTANCE OF 38.10' TO A POINT FOR CORNER;
THENCE S 58° 35' 10" E, A DISTANCE OF 144.47' TO A POINT FOR CORNER;
THENCE S 68° 36' 37" E, A DISTANCE OF 92.81' TO A POINT FOR CORNER;
THENCE S 86° 12' 52" E, A DISTANCE OF 287.67' TO A POINT FOR CORNER;
THENCE S 01° 09' 43" W, A DISTANCE OF 1148.58' TO A POINT FOR CORNER;
THENCE S 89° 32' 24" E, A DISTANCE OF 821.05' TO A POINT FOR CORNER;
THENCE N 50° 06' 36" E, A DISTANCE OF 396.00' TO A POINT FOR CORNER;
THENCE N 11° 16' 12" E, A DISTANCE OF 218.18' TO A POINT FOR CORNER;

THENCE N 49° 09' 00" E, A DISTANCE OF 386.58' TO A POINT FOR CORNER;
THENCE N 14° 00' 36" E, A DISTANCE OF 376.45' TO A POINT FOR CORNER;
THENCE S 82° 33' 36" E, A DISTANCE OF 107.84' TO A POINT FOR CORNER;
THENCE S 36° 20' 24" E, A DISTANCE OF 445.50' TO A POINT FOR CORNER;
THENCE S 01° 19' 48" W, A DISTANCE OF 319.90' TO A POINT FOR CORNER;
THENCE S 88° 54' 04" E, A DISTANCE OF 211.88' TO A POINT FOR CORNER;
THENCE S 48° 03' 04" E, A DISTANCE OF 62.17' TO A POINT FOR CORNER;
THENCE S 84° 11' 01" E, A DISTANCE OF 55.99' TO A POINT FOR CORNER;
THENCE N 88° 24' 22" E, A DISTANCE OF 463.75' TO A POINT FOR CORNER;
THENCE S 00° 10' 35" W, A DISTANCE OF 209.46' TO A POINT FOR CORNER;
THENCE S 83° 57' 03" E, A DISTANCE OF 147.85' TO A POINT FOR CORNER;
THENCE S 77° 30' 52" E, A DISTANCE OF 114.00' TO A POINT FOR CORNER;
THENCE S 76° 32' 42" E, A DISTANCE OF 193.23' TO A POINT FOR CORNER;
THENCE S 76° 32' 42" E, A DISTANCE OF 364.76' TO A POINT FOR CORNER;
THENCE S 14° 10' 41" W, A DISTANCE OF 551.87' TO A POINT FOR CORNER;
THENCE S 08° 25' 38" W, A DISTANCE OF 60.26' TO A POINT FOR CORNER;
THENCE S 54° 58' 06" E, A DISTANCE OF 174.36' TO A POINT FOR CORNER;
THENCE S 31° 09' 34" E, A DISTANCE OF 221.88' TO A POINT FOR CORNER;
THENCE S 34° 59' 31" W, A DISTANCE OF 35.93' TO A POINT FOR CORNER;
THENCE S 48° 00' 45" E, A DISTANCE OF 59.41' TO A POINT FOR CORNER;
THENCE S 05° 21' 21" W, A DISTANCE OF 47.31' TO A POINT FOR CORNER;
THENCE S 62° 52' 43" E, A DISTANCE OF 67.80' TO A POINT FOR CORNER;
THENCE S 32° 03' 28" E, A DISTANCE OF 85.97' TO A POINT FOR CORNER;
THENCE S 11° 08' 11" E, A DISTANCE OF 190.51' TO A POINT FOR CORNER;
THENCE S 28° 53' 12" E, A DISTANCE OF 97.50' TO A POINT FOR CORNER;

THENCE S 39° 03' 46" E, A DISTANCE OF 130.80' TO A POINT FOR CORNER;
THENCE S 35° 56' 31" E, A DISTANCE OF 145.44' TO A POINT FOR CORNER;
THENCE S 79° 10' 39" E, A DISTANCE OF 101.90' TO A POINT FOR CORNER;
THENCE N 44° 15' 56" E, A DISTANCE OF 162.37' TO A POINT FOR CORNER;
THENCE N 45° 27' 04" E, A DISTANCE OF 198.27' TO A POINT FOR CORNER;
THENCE N 58° 20' 21" E, A DISTANCE OF 77.05' TO A POINT FOR CORNER;
THENCE N 58° 12' 53" E, A DISTANCE OF 163.53' TO A POINT FOR CORNER;
THENCE N 64° 38' 55" E, A DISTANCE OF 201.36' TO A POINT FOR CORNER;
THENCE N 66° 10' 53" E, A DISTANCE OF 158.26' TO A POINT FOR CORNER;
THENCE N 74° 52' 32" E, A DISTANCE OF 56.41' TO A POINT FOR CORNER;
THENCE N 67° 03' 04" E, A DISTANCE OF 177.42' TO A POINT FOR CORNER;
THENCE N 03° 05' 39" E, A DISTANCE OF 218.15' TO A POINT FOR CORNER;
THENCE N 71° 22' 20" W, A DISTANCE OF 138.24' TO A POINT FOR CORNER;
THENCE N 68° 03' 24" W, A DISTANCE OF 220.57' TO A POINT FOR CORNER;
THENCE N 76° 43' 11" W, A DISTANCE OF 243.48' TO A POINT FOR CORNER;
THENCE N 65° 00' 35" W, A DISTANCE OF 191.62' TO A POINT FOR CORNER;
THENCE N 17° 29' 18" W, A DISTANCE OF 112.65' TO A POINT FOR CORNER;
THENCE N 26° 13' 56" E, A DISTANCE OF 113.22' TO A POINT FOR CORNER;
THENCE N 88° 21' 14" E, A DISTANCE OF 256.21' TO A POINT FOR CORNER;
THENCE S 79° 50' 52" E, A DISTANCE OF 105.65' TO A POINT FOR CORNER;
THENCE S 80° 53' 18" E, A DISTANCE OF 49.71' TO A POINT FOR CORNER;
THENCE S 85° 18' 51" E, A DISTANCE OF 90.08' TO A POINT FOR CORNER;
THENCE N 71° 48' 59" E, A DISTANCE OF 212.24' TO A POINT FOR CORNER;
THENCE S 60° 31' 29" E, A DISTANCE OF 38.89' TO A POINT FOR CORNER;
THENCE N 88° 27' 07" E, A DISTANCE OF 108.96' TO A POINT FOR CORNER;

THENCE N 68° 54' 08" E, A DISTANCE OF 200.36' TO A POINT FOR CORNER;
THENCE N 00° 00' 00" W, A DISTANCE OF 42.68' TO A POINT FOR CORNER;
THENCE N 39° 48' 20" E, A DISTANCE OF 68.97' TO A POINT FOR CORNER;
THENCE N 53° 35' 01" E, A DISTANCE OF 111.57' TO A POINT FOR CORNER;
THENCE N 07° 01' 42" E, A DISTANCE OF 108.26' TO A POINT FOR CORNER;
THENCE N 08° 23' 34" W, A DISTANCE OF 90.76' TO A POINT FOR CORNER;
THENCE N 64° 10' 44" W, A DISTANCE OF 50.69' TO A POINT FOR CORNER;
THENCE N 27° 48' 06" W, A DISTANCE OF 91.52' TO A POINT FOR CORNER;
THENCE N 77° 45' 51" W, A DISTANCE OF 125.00' TO A POINT FOR CORNER;
THENCE S 72° 07' 18" W, A DISTANCE OF 143.83' TO A POINT FOR CORNER;
THENCE N 75° 57' 49" W, A DISTANCE OF 91.03' TO A POINT FOR CORNER;
THENCE S 65° 33' 21" W, A DISTANCE OF 35.57' TO A POINT FOR CORNER;
THENCE N 69° 34' 02" W, A DISTANCE OF 160.21' TO A POINT FOR CORNER;
THENCE N 36° 39' 56" W, A DISTANCE OF 165.14' TO A POINT FOR CORNER;
THENCE N 37° 35' 26" W, A DISTANCE OF 234.04' TO A POINT FOR CORNER;
THENCE N 40° 26' 59" W, A DISTANCE OF 301.73' TO A POINT FOR CORNER;
THENCE N 80° 32' 15" E, A DISTANCE OF 53.72' TO A POINT FOR CORNER;
THENCE S 64° 28' 13" E, A DISTANCE OF 109.28' TO A POINT FOR CORNER;
THENCE S 83° 44' 11" E, A DISTANCE OF 121.42' TO A POINT FOR CORNER;
THENCE S 87° 35' 21" E, A DISTANCE OF 139.95' TO A POINT FOR CORNER;
THENCE N 56° 06' 14" E, A DISTANCE OF 113.49' TO A POINT FOR CORNER;
THENCE N 41° 55' 21" E, A DISTANCE OF 96.93' TO A POINT FOR CORNER;
THENCE N 69° 29' 31" E, A DISTANCE OF 205.86' TO A POINT FOR CORNER;
THENCE N 49° 49' 15" E, A DISTANCE OF 86.69' TO A POINT FOR CORNER;
THENCE N 40° 09' 21" W, A DISTANCE OF 61.63' TO A POINT FOR CORNER;

THENCE N 27° 27' 40" W, A DISTANCE OF 134.69' TO A POINT FOR CORNER;
THENCE N 85° 17' 07" W, A DISTANCE OF 143.26' TO A POINT FOR CORNER;
THENCE S 88° 48' 53" W, A DISTANCE OF 213.47' TO A POINT FOR CORNER;
THENCE S 78° 06' 41" W, A DISTANCE OF 114.31' TO A POINT FOR CORNER;
THENCE N 56° 53' 22" W, A DISTANCE OF 40.42' TO A POINT FOR CORNER;
THENCE N 40° 14' 11" W, A DISTANCE OF 50.13' TO A POINT FOR CORNER;
THENCE N 33° 01' 25" W, A DISTANCE OF 35.11' TO A POINT FOR CORNER;
THENCE N 10° 18' 19" W, A DISTANCE OF 49.37' TO A POINT FOR CORNER;
THENCE N 00° 00' 00" W, A DISTANCE OF 47.10' TO A POINT FOR CORNER;
THENCE N 39° 48' 20" E, A DISTANCE OF 68.97' TO A POINT FOR CORNER;
THENCE N 27° 08' 59" E, A DISTANCE OF 64.51' TO A POINT FOR CORNER;
THENCE N 53° 41' 44" E, A DISTANCE OF 89.49' TO A POINT FOR CORNER;
THENCE N 20° 04' 18" E, A DISTANCE OF 81.49' TO A POINT FOR CORNER;
THENCE N 19° 20' 40" W, A DISTANCE OF 146.63' TO A POINT FOR CORNER;
THENCE N 01° 45' 45" E, A DISTANCE OF 39.37' TO A POINT FOR CORNER;
THENCE N 23° 04' 43" E, A DISTANCE OF 57.08' TO A POINT FOR CORNER;
THENCE N 81° 29' 31" E, A DISTANCE OF 35.68' TO A POINT FOR CORNER;
THENCE S 81° 36' 26" E, A DISTANCE OF 45.38' TO A POINT FOR CORNER;
THENCE N 51° 49' 05" E, A DISTANCE OF 96.43' TO A POINT FOR CORNER;
THENCE N 42° 26' 11" E, A DISTANCE OF 69.80' TO A POINT FOR CORNER;
THENCE N 29° 44' 42" W, A DISTANCE OF 47.47' TO A POINT FOR CORNER;
THENCE N 11° 33' 36" E, A DISTANCE OF 66.10' TO A POINT FOR CORNER;
THENCE N 17° 44' 42" E, A DISTANCE OF 77.27' TO A POINT FOR CORNER;
THENCE N 16° 47' 55" W, A DISTANCE OF 81.49' TO A POINT FOR CORNER;
THENCE N 71° 33' 54" W, A DISTANCE OF 46.54' TO A POINT FOR CORNER;

THENCE N 26° 33' 55" W, A DISTANCE OF 29.62' TO A POINT FOR CORNER;
THENCE N 00° 00' 02" W, A DISTANCE OF 29.44' TO A POINT FOR CORNER;
THENCE S 70° 29' 59" W, A DISTANCE OF 463.35' TO A POINT FOR CORNER;
THENCE S 42° 25' 06" W, A DISTANCE OF 338.77' TO A POINT FOR CORNER;
THENCE S 00° 28' 03" W, A DISTANCE OF 49.79' TO A POINT FOR CORNER;
THENCE S 87° 03' 38" W, A DISTANCE OF 188.27' TO A POINT FOR CORNER;
THENCE N 02° 45' 44" W, A DISTANCE OF 215.95' TO A POINT FOR CORNER;
THENCE S 87° 15' 50" W, A DISTANCE OF 211.65' TO A POINT FOR CORNER;
THENCE N 02° 16' 12" E, A DISTANCE OF 232.08' TO A POINT FOR CORNER;
THENCE N 02° 21' 17" W, A DISTANCE OF 288.96' TO A POINT FOR CORNER;
THENCE N 88° 07' 12" W, A DISTANCE OF 189.90' TO A POINT FOR CORNER;
THENCE N 15° 38' 14" W, A DISTANCE OF 102.38' TO A POINT FOR CORNER;
THENCE N 43° 53' 06" W, A DISTANCE OF 948.71' TO A POINT FOR CORNER;
THENCE N 00° 21' 43" E, A DISTANCE OF 209.54' TO A POINT FOR CORNER;
THENCE N 89° 21' 00" E, A DISTANCE OF 208.70' TO A POINT FOR CORNER;
THENCE S 00° 04' 16" W, A DISTANCE OF 207.04' TO A POINT FOR CORNER;
THENCE N 88° 36' 41" E, A DISTANCE OF 415.10' TO A POINT FOR CORNER;
THENCE N 89° 12' 18" E, A DISTANCE OF 118.07' TO A POINT FOR CORNER;
THENCE N 73° 48' 39" E, A DISTANCE OF 580.20' TO A POINT FOR CORNER;
THENCE N 29° 30' 34" W, A DISTANCE OF 991.56' TO A POINT FOR CORNER;
THENCE N 08° 58' 21" W, A DISTANCE OF 20.04' TO A POINT FOR CORNER;
THENCE S 88° 49' 43" W, A DISTANCE OF 140.13' TO A POINT FOR CORNER;
THENCE N 88° 50' 12" W, A DISTANCE OF 77.97' TO A POINT FOR CORNER;
THENCE N 87° 00' 35" W, A DISTANCE OF 214.26' TO A POINT FOR CORNER;
THENCE N 03° 36' 19" E, A DISTANCE OF 109.33' TO A POINT FOR CORNER;

THENCE N 89° 23' 51" W, A DISTANCE OF 373.40' TO A POINT FOR CORNER;
THENCE N 00° 30' 00" W, A DISTANCE OF 222.46' TO A POINT FOR CORNER;
THENCE N 87° 15' 00" W, A DISTANCE OF 125.82' TO A POINT FOR CORNER;
THENCE N 02° 09' 36" W, A DISTANCE OF 450.12' TO A POINT FOR CORNER;
THENCE N 58° 32' 38" W, A DISTANCE OF 273.78' TO A POINT FOR CORNER;
THENCE N 02° 28' 48" E, A DISTANCE OF 166.53' TO A POINT FOR CORNER;
THENCE N 28° 28' 48" E, A DISTANCE OF 120.00' TO A POINT FOR CORNER;
THENCE N 01° 33' 36" E, A DISTANCE OF 47.00' TO A POINT FOR CORNER;
THENCE N 88° 14' 45" W, A DISTANCE OF 74.04' TO A POINT FOR CORNER;
THENCE S 89° 09' 23" W, A DISTANCE OF 406.51' TO A POINT FOR CORNER;
THENCE S 89° 09' 23" W, A DISTANCE OF 57.24' TO A POINT FOR CORNER;
THENCE N 01° 17' 09" W, A DISTANCE OF 398.77' TO A POINT FOR CORNER;
THENCE N 56° 51' 13" E, A DISTANCE OF 300.69' TO A POINT FOR CORNER;
THENCE N 01° 11' 11" W, A DISTANCE OF 764.79' TO A POINT FOR CORNER;
THENCE N 49° 19' 30" W, A DISTANCE OF 180.35' TO A POINT FOR CORNER;
THENCE N 58° 03' 29" W, A DISTANCE OF 70.47' TO A POINT FOR CORNER;
THENCE N 78° 12' 40" W, A DISTANCE OF 93.69' TO A POINT FOR CORNER;
THENCE N 89° 35' 31" W, A DISTANCE OF 99.93' TO A POINT FOR CORNER;
THENCE N 56° 24' 07" W, A DISTANCE OF 59.67' TO A POINT FOR CORNER;
THENCE N 00° 25' 22" E, A DISTANCE OF 35.70' TO A POINT FOR CORNER;
THENCE N 71° 53' 32" E, A DISTANCE OF 52.96' TO A POINT FOR CORNER;
THENCE S 89° 02' 59" E, A DISTANCE OF 127.80' TO A POINT FOR CORNER;
THENCE S 77° 11' 02" E, A DISTANCE OF 83.60' TO A POINT FOR CORNER;
THENCE S 64° 22' 35" E, A DISTANCE OF 55.83' TO A POINT FOR CORNER;
THENCE S 54° 07' 48" E, A DISTANCE OF 55.83' TO A POINT FOR CORNER;

THENCE N 13° 57' 39" E, A DISTANCE OF 459.85' TO A POINT FOR CORNER;
THENCE S 83° 43' 21" E, A DISTANCE OF 110.11' TO A POINT FOR CORNER;
THENCE S 89° 18' 21" E, A DISTANCE OF 167.55' TO A POINT FOR CORNER;
THENCE S 89° 18' 21" E, A DISTANCE OF 182.84' TO A POINT FOR CORNER;
THENCE S 01° 15' 29" W, A DISTANCE OF 72.44' TO A POINT FOR CORNER;
THENCE S 46° 21' 00" W, A DISTANCE OF 180.00' TO A POINT FOR CORNER;
THENCE S 30° 00' 00" E, A DISTANCE OF 278.46' TO A POINT FOR CORNER;
THENCE S 30° 00' 00" E, A DISTANCE OF 131.54' TO A POINT FOR CORNER;
THENCE N 88° 00' 00" E, A DISTANCE OF 75.00' TO A POINT FOR CORNER;
THENCE S 86° 13' 12" E, A DISTANCE OF 80.00' TO A POINT FOR CORNER;
THENCE N 69° 24' 36" E, A DISTANCE OF 233.35' TO A POINT FOR CORNER;
THENCE N 22° 18' 00" E, A DISTANCE OF 110.00' TO A POINT FOR CORNER;
THENCE S 23° 18' 00" E, A DISTANCE OF 131.00' TO A POINT FOR CORNER;
THENCE S 40° 00' 00" W, A DISTANCE OF 128.00' TO A POINT FOR CORNER;
THENCE S 89° 21' 36" W, A DISTANCE OF 475.00' TO A POINT FOR CORNER;
THENCE N 67° 57' 39" W, A DISTANCE OF 147.58' TO A POINT FOR CORNER;
THENCE S 00° 57' 48" W, A DISTANCE OF 94.16' TO A POINT FOR CORNER;
THENCE N 89° 24' 06" E, A DISTANCE OF 696.72' TO A POINT FOR CORNER;
THENCE S 07° 28' 34" E, A DISTANCE OF 531.19' TO A POINT FOR CORNER;
THENCE S 61° 17' 11" E, A DISTANCE OF 250.77' TO A POINT FOR CORNER;
THENCE S 28° 31' 25" E, A DISTANCE OF 29.32' TO A POINT FOR CORNER;
THENCE S 28° 31' 26" E, A DISTANCE OF 503.48' TO A POINT FOR CORNER;
THENCE S 89° 28' 17" E, A DISTANCE OF 502.00' TO A POINT FOR CORNER;
THENCE N 00° 00' 00" W, A DISTANCE OF 457.40' TO A POINT FOR CORNER;
THENCE N 00° 34' 13" W, A DISTANCE OF 642.56' TO A POINT FOR CORNER;

THENCE N 90° 00' 00" E, A DISTANCE OF 766.59' TO A POINT FOR CORNER;
THENCE N 00° 00' 00" W, A DISTANCE OF 270.00' TO A POINT FOR CORNER;
THENCE N 90° 00' 00" W, A DISTANCE OF 269.81' TO A POINT FOR CORNER;
THENCE N 35° 07' 59" W, A DISTANCE OF 572.47' TO A POINT FOR CORNER;
THENCE N 08° 06' 37" W, A DISTANCE OF 437.78' TO A POINT FOR CORNER;
THENCE N 89° 50' 46" E, A DISTANCE OF 265.44' TO A POINT FOR CORNER;
THENCE S 88° 17' 22" E, A DISTANCE OF 208.47' TO A POINT FOR CORNER;
THENCE N 13° 12' 21" W, A DISTANCE OF 658.24' TO A POINT FOR CORNER;
THENCE N 89° 56' 18" W, A DISTANCE OF 391.95' TO A POINT FOR CORNER;
THENCE N 88° 17' 35" W, A DISTANCE OF 433.72' TO A POINT FOR CORNER;
THENCE N 00° 23' 43" W, A DISTANCE OF 1127.51' TO A POINT FOR CORNER;
THENCE N 01° 05' 16" E, A DISTANCE OF 1654.74' TO A POINT FOR CORNER;
THENCE N 01° 05' 16" E, A DISTANCE OF 181.70' TO A POINT FOR CORNER;
THENCE N 01° 05' 16" E, A DISTANCE OF 265.95' TO A POINT FOR CORNER;
THENCE S 89° 36' 47" E, A DISTANCE OF 2127.00' TO A POINT FOR CORNER;
THENCE S 89° 15' 16" E, A DISTANCE OF 1207.25' TO A POINT FOR CORNER;
THENCE S 00° 02' 37" W, A DISTANCE OF 719.59' TO A POINT FOR CORNER;
THENCE N 90° 00' 00" E, A DISTANCE OF 2285.77' TO A POINT FOR CORNER;
THENCE N 89° 44' 38" E, A DISTANCE OF 654.68' TO A POINT FOR CORNER;
THENCE N 89° 44' 38" E, A DISTANCE OF 612.09' TO A POINT FOR CORNER;
THENCE S 30° 18' 45" E, A DISTANCE OF 212.86' TO A POINT FOR CORNER;
THENCE S 08° 08' 52" E, A DISTANCE OF 278.98' TO A POINT FOR CORNER;
THENCE S 09° 38' 53" E, A DISTANCE OF 139.49' TO A POINT FOR CORNER;
THENCE S 11° 08' 15" E, A DISTANCE OF 276.09' TO A POINT FOR CORNER;
THENCE S 28° 30' 01" E, A DISTANCE OF 100.17' TO A POINT FOR CORNER;

THENCE S 15° 30' 01" E, A DISTANCE OF 100.17' TO A POINT FOR CORNER;
THENCE S 02° 30' 01" E, A DISTANCE OF 100.17' TO A POINT FOR CORNER;
THENCE S 10° 29' 59" W, A DISTANCE OF 100.17' TO A POINT FOR CORNER;
THENCE S 23° 29' 59" W, A DISTANCE OF 100.17' TO A POINT FOR CORNER;
THENCE S 36° 29' 27" W, A DISTANCE OF 100.03' TO A POINT FOR CORNER;
THENCE S 24° 24' 24" W, A DISTANCE OF 381.52' TO A POINT FOR CORNER;
THENCE S 21° 24' 24" W, A DISTANCE OF 381.52' TO A POINT FOR CORNER;
THENCE S 18° 48' 05" W, A DISTANCE OF 281.10' TO A POINT FOR CORNER;
THENCE S 02° 12' 10" W, A DISTANCE OF 114.13' TO A POINT FOR CORNER;
THENCE N 89° 55' 22" W, A DISTANCE OF 17.05' TO A POINT FOR CORNER;
THENCE S 23° 35' 11" W, A DISTANCE OF 234.23' TO A POINT FOR CORNER;
THENCE S 20° 05' 50" W, A DISTANCE OF 214.23' TO A POINT FOR CORNER;
THENCE S 15° 50' 59" W, A DISTANCE OF 312.82' TO A POINT FOR CORNER;
THENCE S 10° 20' 59" W, A DISTANCE OF 375.33' TO A POINT FOR CORNER;
THENCE S 04° 51' 00" W, A DISTANCE OF 312.82' TO A POINT FOR CORNER;
THENCE S 00° 09' 01" E, A DISTANCE OF 312.82' TO A POINT FOR CORNER;
THENCE S 03° 24' 19" E, A DISTANCE OF 94.51' TO THE POINT OF BEGINNING AND CONTAINING
174,669,895 SQUARE FEET, OR 4009.87 ACRES OF LAND, MORE OR LESS.